

III. In the Claims.

1. Please cancel claims 6, 7, 9-12, 14, 15 without prejudice or disclaimer of subject matter.
2. Please amend claims 1, 13, 19 as follows:
 1. (Amended) An automotive signal lens system comprising:
 - a light source;
 - a reflective surface;
 - a plurality of light transmitting elements arranged adjacent and parallel to each other to form a layer;
 - the layer embedded in a vehicle structural component;
 - a first line drawn between adjacent light transmitting elements when bisected by a second line normal to the first line drawn from a tangent point on a third light transmitting element, the second line having a length d_2 ;
 - the light transmitting elements each having a diameter d_1 ; and $d_2 < d_1$; and
 - the light source located between the reflective surface and the layer.
 2. (Original) The signal lens as in claim 1, wherein the light transmitting elements each have a central axis that is inclined to a reflective surface at an angle in the range of 0° to 45° .
 3. (Original) The signal lens as in claim 2 further comprising a plurality of light sources.
 4. (Original) The signal lens as in claim 3 wherein each light source is aligned with at least one light transmitting element.
 5. (Original) The signal lens as in claim 4, wherein an outer surface of each light transmitting element is coplanar with each adjacent light transmitting element outer surface.
 6. (Cancelled).

7. (Cancelled).
8. (Previously cancelled).
9. (Cancelled).
10. (Cancelled).
11. (Cancelled).
12. (Cancelled).
13. (Amended) A vehicle signal lens system comprising:
 - a light source;
 - a reflective surface;
 - the light source disposed between the reflective surface and
 - the light emitting surface;
 - a light emitting surface illuminated by the light source;
 - the light emitting surface further comprises light transmitting
 - elements each having a central axis and each inclined to the
 - reflective surface at an angle greater than 0° and less than or equal
 - to 45°;
 - the light emitting surface integral to a vehicle surface;
 - the vehicle surface transparent to a light transmitted from the
 - light emitting surface; and
 - the light emitting surface is not substantially visually
 - distinguishable from the vehicle surface when the light source is
 - not illuminated.
14. (Cancelled).
15. (Cancelled).
16. (Previously Amended) A vehicle signal lens system comprising:
 - a light source;
 - a reflective surface;

a plurality of light transmitting elements arranged adjacent and parallel to each other to form a substantially planar layer;

the light source located between the reflective surface and the planar layer; and

a first line drawn between adjacent light transmitting elements when bisected by a second line normal to the first line drawn from a tangent point on a third light transmitting element, the second line having a length d_2 , the light transmitting elements each having a diameter d_1 , and $d_2 < d_1$.

17. (Previously Amended) A vehicle signal lens system comprising:

a light source;

a reflective surface;

a plurality of fiber optic strands molded into a member material and arranged substantially adjacent to and substantially parallel to each other to form a substantially planar layer; and

the light source located between the reflective surface and the planar layer;

a first line drawn between adjacent fiber optic strands when bisected by a second line normal to the first line drawn from a tangent point on a third fiber optic strand, the second line having a length d_2 , the fiber optic strands each having a diameter d_1 , and $d_2 < d_1$.

18. (Original) The signal lens as in claim 17, wherein the fiber optic strands each have a central axis that is inclined to a reflective surface at an angle in the range of 0° to 45° .

19. (Amended) The signal lens as in claim 17 ~~13~~ wherein the member surface further comprises a tint.